# PHILIPS

## Horticulture LED Solutions

GreenPower LED interlighting

# The right light and energy efficiency for year-round production

Whether you are a high wire grower in the United Kingdom, Finland, Canada or France, get a better, more energy efficient lighting solution to grow right through the darker periods during the year. Based on input from growers around the world, our GreenPower LED interlighting allows you to grow and harvest fresh and flavorful vegetables and fruits year round, no matter where you are or what energy prices you face. Placing light between your plants lets you achieve the maximum value and return from your production and your electricity costs for lighting.

#### Plug and play system reduces installation costs

The interlighting system comes with an easy plug and play connector and just a few cables and accessories. Connect up to 64\* interlighting modules with just one power connection, and save time, materials needed and installation costs, and bring the total cost of project installation down significantly.

The complete system can easily be lifted with one meter at a time, because of the flexible cable connection which again will save time and hassle. With the sidewards light distribution pattern, the leaves can optimally transform the light into growing more yield. The shape of the GreenPower LED interlighting module is designed to minimize maintenance.

### **Key benefits**

- Boost production by applying the right light at the right spot with a system efficacy of up to 3.3 µmol/J.
- Minimize your energy costs by choosing the most efficient interlighting module for your situation.
- Reduce installation costs thanks to daisy-chaining and plug and play design.
- Easy to install and maintain.

## Choose the best value for your situation



Specifications		2.5 m / 98"		2 m / 80"		
		RO	но	RO	но	
Typical photon flux	µmol/s	220	300	175	240	
Power consumption (max)	w	79	92	64	74	
Efficacy	µmol/J	2.8	3.3	2.7	3.2	
Dimensions	cm	6.5 x 7.96.5 x 7.92.55 x 3.112.55 x 3.11		6.5 x 7.9	7.9	
	inch			1		
Weight (driver included)	kg	2.5		2.2		
Input Voltage <sup>1</sup>	VAC	200 - 400				
Power factor		> 0.9				
Rated Average Lifetime <sup>2</sup>	hrs	36.000 L90				
Ingress protection rating		IP66 damp/dry				
Approval marks		CE, PSE, UL/CSA				
Accessories		Full range of brackets available for easy and quick installation				

RO = regular output HO = high output

<sup>1</sup> 50-60 Hz

<sup>2</sup> Lifetime and maintenance values are given at an ambient temperature of 25°C/77°F. All measured lifetimes are industry standard measurements indicating average length of operation and not a performance claim specific to any individual product.



© 2020 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

Document order number: 4422 944 08019 E 03/2020 | Data subject to change Placing lighting within the canopy of your high wire plants directs and focuses growth-stimulating light on the most vital part of the crop. You can then get the most out of your crop with a reduced energy usage during the complete lifetime of your interlighting.

To help you get the best solution for your situation, we offer two versions of the GreenPower LED interlighting system.

In case you are a grower and want to apply the highest amount of light possible and get the most yield possible, you would best install the GreenPower LED interlighting module high output version with 300 µmol/s light output and a system efficacy of 3.3 µmol/J.

The interlighting module with 220 µmol/s light output and 2.8 µmol/J light efficiency gives you exactly what you need to increase your yields, when you are facing high energy costs, and can be especially beneficial for increasing yields of e.g. tomatoes and cucumbers, which are not affected by higher light levels.

The system comes in a 2 meter and 2.5 meter version, allowing you to tailor it to your specific situation and get a uniform light distribution right until the end of each row.



For more information about Philips Horticulture LED Solutions visit: www.philips.com/horti

Write us an e-mail: horti.info@signify.com

Or tweet us: @PhilipsHorti